



9430

Remote Area Lighting System

- Built Pelican tough
- New improved version Generation 3
- Up to 15 hours of run time
- 3000 lumens of brightness
- Maintenance Free LED Array with life expectancy of 50,000 hours
- Fully extendable mast with 360 degree rotating head
- Low Battery Warning System
- Waterproof Rubber Activation Switch
- Mast Extension Lock

CONFIGURATIONS

9430 - Standard

DIMENSIONS

Head (L x W x D): 6.50 x 7.87" x 2.56 (16.5 x 20 x 6.5 cm) Closed (L x W x D): 15.75 x 7.87" x 9.06 (40 x 20 x 23 cm)

Mast Length: 32.28" Cord Length: 13.78"

MATERIALS

Body: Polycarbonate (PC) / ABS Head: Polycarbonate (PC) / ABS Mast: Glass-Reinforced Plastic Lens: Polycarbonate (PC)

COLORS



Black



Yellow

LIGHT SPECS

Lumens (High): 3000 Lumens (Low): 1500 Lamp Heads: 1 Lamp Type: LED Number of LEDs: 6 Lamp Life: 50000 hrs Beam Spread: 125° IP Rating: 54

POWER

Run Time (High): 8.00 hrs Run Time (Low): 15.00 hrs

Battery Type: Sealed Lead Acid (SLA)

Battery Lifespan: 500 cycles **Charge Time**: 300 mins

Battery Level Indicator: Intermittent Blinking

Sockets (Primary): 1 Sockets (Aux): 1 Volts: 12.0v

WEIGHT

Weight: 22.65 lbs

SWITCH

Switch Type: Silicone Rubber Keypad

CERTIFICATIONS

RoHS Compliant CE Approved

Pelican Products, Inc.

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311 sales@pelican.com • www.pelican.com