



Product description: 46892 SP 35W 12V GU4 10X1 OSRAM
 Product code: 4050300529349
 Quantity: Folding carton box (FS) contains 1 Piece (PCE)

You can find this product in the eCatalog:

http://catalog.myosram.com?~language=EN&~country=COM&it_p=4050300529349

Capabilities	
Dimmable	Yes
Burning position	hs30

Additional product data	
Base (standard designation)	GU4
Design / version	Reflector

Colors & materials	
Rated lamp mercury content	0.0 mg
Mercury-free	Yes

Electrical data	
Rated wattage	35 W
Nominal wattage	35 W
Nominal voltage	12 V
Rated number of switching cycles	1000000 ¹⁾
Rated power factor λ	1.00

Dimensions & weight	
Overall length	42.0 mm
Diameter	35.0 mm
Outer bulb	MR35

Lifespan	
Nominal lamp life time	4000 h
Rated lamp life time	4000 h

Light technical data	
Luminous intensity	6200 cd
Beam angle	10 °
Rated color temperature	3000 K
Rated color rendering index Ra	100
Rated starting time	0.0 s
Rated warm-up time (60 %)	0 s
Lumen main.fact.at end of nom.life time	0.80

Packaging units				
Product code	Packaging type and content	Dimensions in h x w x l	Gross weight	Volume
4050300529349	Folding carton box contains 1 Piece	34,000 mm x 34,000 mm x 50,000 mm	17,000 g (0,000 g)	0.058 Cubic dec.
4050300529356	Shipping carton box contains 10 Piece	81,000 mm x 58,000 mm x 178,000 mm	220,000 g (0,000 g)	0.836 Cubic dec.



product details

46892 SP 35W 12V GU4 10X1

OSRAM

DECOSTAR 35 TITAN offers constant luminous intensity, making it ideal for professional applications. The average life of this dichroic reflector lamp is twice as high as many standard products. Thanks to a special reflector coating the luminous intensity and color impression remain constant throughout the full average life of 4,000 hours.

• Brilliant accent light • Constant bluish appearance of the light escaping at the back of the reflector • Dichroic reflector reduces the heat in the light beam by up to 66 % • Constant luminous intensity and color location throughout their life • Flat clear shield • Approved for use in open luminaires to IEC 60598-1 • Average life: 4,000 h • Dimmable • $R_a=100$ • Color temperature: 3,000 K • Base: GU4 • UV filter
For light distribution curves go to www.osram.com

¹⁾ At 1 s on / 1 s off