



Product description: 46892 WFL 35W 12V GU4 10X1 OSRAM
 Product code: 4050300529363
 Quantity: Folding carton box (FS) contains 1 Piece (PCE)

You can find this product in the eCatalog:

http://catalog.myosram.com?~language=EN&~country=COM&it_p=4050300529363

| Capabilities | | | | |
|---|-------------------------------------|-----------------------------------|--------------------|------------------|
| Dimmable | Yes | | | |
| Burning position | hs30 | | | |
| Country specific categorizations | | | | |
| ILCOS | HRGS//UB-35-12-GU4-35,3/36 | | | |
| Additional product data | | | | |
| Base (standard designation) | GU4 | | | |
| Design / version | Reflector | | | |
| Colors & materials | | | | |
| Rated lamp mercury content | 0.0 mg | | | |
| Mercury-free | Yes | | | |
| Electrical data | | | | |
| Rated wattage | 35 W | | | |
| Nominal wattage | 35 W | | | |
| Nominal voltage | 12 V | | | |
| Rated number of switching cycles | 1000000 ¹⁾ | | | |
| Rated power factor λ | 1.00 | | | |
| Dimensions & weight | | | | |
| Overall length | 42.0 mm | | | |
| Diameter | 35.0 mm | | | |
| Outer bulb | MR35 | | | |
| Lifespan | | | | |
| Nominal lamp life time | 4000 h | | | |
| Rated lamp life time | 4000 h | | | |
| Light technical data | | | | |
| Luminous intensity | 1400 cd | | | |
| Beam angle | 36 ° | | | |
| Rated color temperature | 3000 K | | | |
| Rated color rendering index Ra | 100 | | | |
| Rated starting time | 0.0 s | | | |
| Rated warm-up time (60 %) | 0 s | | | |
| Lumen main.fact.at end of nom.life time | 0.80 | | | |
| Packaging units | | | | |
| Product code | Packaging type and content | Dimensions in h x w x l | Gross weight | Volume |
| 4050300529363 | Folding carton box contains 1 Piece | 34,000 mm x 29,000 mm x 50,000 mm | 18,000 g (0,000 g) | 0,058 Cubic dec. |



| Packaging units | | | | |
|-----------------|---------------------------------------|------------------------------------|---------------------|------------------|
| Product code | Packaging type and content | Dimensions in h x w x l | Gross weight | Volume |
| 4050300529370 | Shipping carton box contains 10 Piece | 63,000 mm x 81,000 mm x 178,000 mm | 206,000 g (0,000 g) | 0,908 Cubic dec. |

DECOSTAR 35 TITAN offers constant luminous intensity, making it ideal for professional applications. The average life of this dichroic reflector lamp is twice as high as many standard products. Thanks to a special reflector coating the luminous intensity and color impression remain constant throughout the full average life of 4,000 hours.

• Brilliant accent light • Constant bluish appearance of the light escaping at the back of the reflector • Dichroic reflector reduces the heat in the light beam by up to 66 % • Constant luminous intensity and color location throughout their life • Flat clear shield • Approved for use in open luminaires to IEC 60598-1 • Average life: 4,000 h • Dimmable • $R_a=100$ • Color temperature: 3,000 K • Base: GU4 • UV filter
For light distribution curves go to www.osram.com

¹⁾ At 1 s on / 1 s off