



product details

64425

Product description: 64425
 Product code: 4050300003924
 Quantity: Folding carton box (FS) contains 1 Piece (PCE)

You can find this product in the eCatalog:

http://catalog.myosram.com?~language=EN&~country=COM&it_p=4050300003924

Capabilities	
Dimmable	Yes
Burning position	hs30
Country specific categorizations	
ILCOS	HSGST/C/UB-20-12-G4-10/22
Additional product data	
Base (standard designation)	G4
Filament setting	Transversal
Colors & materials	
Rated lamp mercury content	0.0 mg
Mercury-free	Yes
Electrical data	
Rated wattage	20 W
Nominal wattage	20 W
Nominal voltage	12 V
Rated number of switching cycles	1000000 ¹⁾
Rated power factor λ	1.00
Dimensions & weight	
Length	33.0 mm
Overall length	33.0 mm
Diameter	10.0 mm
Light center length (LCL)	22.0 mm
Outer bulb	T10
Lifespan	
Nominal lamp life time	2000 h
Rated lamp life time	2000 h
Light technical data	
Nominal luminous flux	260 lm
Rated luminous flux	320 lm
Rated color temperature	2800 K
Rated color rendering index Ra	100
Rated starting time	0.0 s
Rated warm-up time (60 %)	0 s
Lumen main.fact.at end of nom.life time	0.80



product details

64425

Packaging units				
Product code	Packaging type and content	Dimensions in h x w x l	Gross weight	Volume
4050300003924	Folding carton box contains 1 Piece	25,000 mm x 23,000 mm x 70,000 mm	16,364 g (0,000 g)	0,040 Cubic dec.
4050300942261	Shipping carton box contains 40 Piece	121,000 mm x 107,000 mm x 144,000 mm	202,625 g (0,000 g)	1,864 Cubic dec.

Lighting solutions that are unlike anything else - that's HALOSTAR from OSRAM. Open halogen lighting systems and unshielded luminaires are no longer a problem. These decorative reliable point light sources bring rooms to life. It is now possible to design, create and present in the finest detail.

• Brilliant accent light • Incredibly small dimensions for revolutionary new luminaire designs • Approved for use in open luminaires to IEC 60598-1 • Average life: 2,000 h • Dimmable • Ra=100 • Color temperature: 10 W/20 W - 2,800 K; 35 W - 2,900 K; 50 W - 3,000 K • Base: G4, GY6.35 • UV filter

¹⁾ At 1 s on / 1 s off