



product details

64440 S 50W 12V GY6,35 40X1 STAR OSRAM

Product description: 64440 S 50W 12V GY6,35 40X1 STAR OSRAM
 Product code: 4050300328201
 Quantity: Folding carton box (FS) contains 1 Piece (PCE)

You can find this product in the eCatalog:

http://catalog.myosram.com?~language=EN&~country=COM&it_p=4050300328201

Capabilities	
Dimmable	Yes
Burning position	hs30
Country specific categorizations	
ILCOS	HSGST/C/UB-50-12-GY6,35-12/30
Additional product data	
Base (standard designation)	GY6.35
Filament setting	Axial
Colors & materials	
Rated lamp mercury content	0.0 mg
Mercury-free	Yes
Electrical data	
Rated wattage	50 W
Nominal wattage	50 W
Nominal voltage	12 V
Rated number of switching cycles	1000000 ¹⁾
Rated power factor λ	1.00
Dimensions & weight	
Length	44.0 mm
Overall length	44.0 mm
Diameter	12.0 mm
Light center length (LCL)	30.0 mm
Outer bulb	T12
Lifespan	
Nominal lamp life time	4000 h
Rated lamp life time	4000 h
Light technical data	
Nominal luminous flux	900 lm
Rated luminous flux	900 lm
Rated color temperature	3000 K
Rated color rendering index Ra	100
Rated starting time	0.0 s
Rated warm-up time (60 %)	0 s
Lumen main.fact.at end of nom.life time	0.80



product details

64440 S 50W 12V GY6,35 40X1 STAR OSRAM

Packaging units				
Product code	Packaging type and content	Dimensions in h x w x l	Gross weight	Volume
4050300328201	Folding carton box contains 1 Piece	25,000 mm x 23,000 mm x 70,000 mm	5,000 g (0,000 g)	0,040 Cubic dec.
4050300942193	Shipping carton box contains 40 Piece	121,000 mm x 126,000 mm x 126,000 mm	208,000 g (0,000 g)	1,864 Cubic dec.

Paving the way for new luminaire designs: HALOSTAR STARLITE from OSRAM. With freeburning halogen lamps and their bright pools of light it is possible to provide accent lighting for entire rooms. Entrance halls and reception rooms appear in a new vibrant light. They may even be transformed by sculptures in light. Their long average life of 4,000 hours is truly impressive.

• Brilliant accent light • Incredibly small dimensions for revolutionary new luminaire designs • Approved for use in open luminaires to IEC 60598-1 • Axial filament for optimum directional light • Special pins for corrosion protection • Average life span: 4,000 h • Dimmable • $R_a=100$ • Color temperature: 5 W/10 W (6 V) - 2,700 K; 10 W/20 W - 2,800 K; 35 W - 2,900 K; 50 W/75 W/90 W - 3,000 K • Base: G4, GY6.35 • UV filter

¹⁾ At 1 s on / 1 s off