



| Description                 | V    | W  | Am-<br>perage | Cap   | Bulb<br>diameter<br>D<br>max. mm | Total<br>length<br>L<br>max. mm | Light<br>centre<br>length<br>mm | Lumi-<br>nous<br>flux<br>lm | Average<br>life<br>h |
|-----------------------------|------|----|---------------|-------|----------------------------------|---------------------------------|---------------------------------|-----------------------------|----------------------|
| 22.8V 40W G6.35 axial 700lm | 22.8 | 40 |               | G6.35 | 11                               | 44                              | 31.25                           | 700                         | 1,000                |
| 22.8V 40W G6.35 transversal | 22.8 | 40 | 1.75          | G6.35 | 12                               | 44                              | 30.5                            | 800                         | 1,000                |
| 22.8V 50W G6.35 axial       | 22.8 | 50 | 2,2           | G6.35 | 11                               | 44                              | 30.5                            | 1,100                       | 700                  |
| 22.8V 50W G6.35 transversal | 22.8 | 50 | 2,2           | G6.35 | 11                               | 44                              | 30.5                            | 950                         | 1,000                |
| 22.8V 50W G6.35 axial       | 22.8 | 50 |               | G6.35 | 11                               | 44                              | 30.5                            |                             |                      |
| Halogen lamp 22.8V 40W AX   | 22.8 | 40 |               | G6.35 | 11                               | 44                              | 30.5                            | 900                         | 800                  |