

MR11

- Only for Use in Approved Enclosed Halogen Fixtures
- Miniature 2-Pin Base - GZ4, 2-Pin Base - G4.8/5.3 & Double Contact Bayonet Base - BA15d
- Low Voltage
- Universal Burn Position
- Faceted (except as noted)



| Watts (W) | Ordering Code | Lamp Description | MOL (mm) | Reflector Type | Filament Type | Color Temp (K) | Beam | | Max CP (cd) | Ave Life (h) | Case Qty |
|-----------------------------------|------------------|------------------------|-------------|-------------------|------------------|----------------------|-------|-------------|----------------|--------------------|-------------|
| | | | | | | | Angle | Spread | | | |
| Miniature 2-Pin Base – GZ4 | | | | | | | | | | | |
| 10 | 1000931 | JCR/M6V-10WN/FG | 40.8 | Faceted | C-6 | 3050 | 8.5° | Narrow Spot | 3000 | 200 | 100 |
| 15 | 1000932 | JCR/M6V-15W/FG/XX MR11 | 35.0 | Faceted | C-6 | 3050 | 17° | Spot | 3900 | 500 | 100 |
| 20 | 1000934 | JCR/M6V-20W | 33.3 | Faceted | C-6 | 3200 | 20° | Spot | 1800 | 50 | 10 |