

HALOGEN LOW VOLTAGE BI-PIN

JC & JCD

- Only for Use in Approved Enclosed Halogen Fixtures
- 2-Pin Base - GY6.35

Watts (W)	Ordering Code	Lamp Description	Dimensions (mm)			Filament Type	Lumens (lm)	Color Temp (K)	Avg Life (h)	Burn Position	Bulb Finish	Case Qty	Fig No
			Dia (A)	MOL (B)	LCL (C)								
2-Pin Base – GY6.35													
35	1000824	JC12V-35W	11.0	44.0	30.0	C-8	650	2900	2000	BD/Hor	Clear	10	1
35	1003486	JC12V-35WF	11.0	44.0	30.0	C-8	650	2900	2000	BD/Hor	Frosted	10	1
35	1000902	JCD120V-35W	11.0	55.0	38.0	CC-2V	500	2800	1500	BD/Hor	Clear	10	2
50	1000827	JC12V-50W	11.0	44.0	30.0	C-6	1000	3000	2000	Univ	Clear	10	3
50	1000828	JC12V-50W	11.0	44.0	30.0	C-8	1000	3000	2000	Univ	Clear	100	3
50	1003487	JC12V-50WF	11.0	44.0	30.0	C-8	1000	3000	2000	Univ	Frosted	10	3
50	1000905	JCD120V-50W	11.0	55.0	38.0	CC-2V	700	2800	1500	BD/Hor	Clear	10	2
75	1000835	JC12V-75W	11.0	44.0	30.0	C-6	1600	3000	2000	Univ	Clear	10	3
100	1000806	JC12V-100W	11.0	44.0	30.0	C-6	2300	3000	2000	Univ	Clear	100	3
100	1000807	JC12V-100WG	11.0	44.0	30.0	C-8	2300	3000	2000	Univ	Clear	100	1
100	1000381	EVA, JC12V-100H20	11.5	44.0	30.0	CBar6	2400	3000	2000	BD/Hor	Clear	10	3
100	1000490	FCR, JC12V-100W	11.0	44.0	30.0	CBar6	3400	3300	50	BD/Hor	Clear	100	3
100	1000507	FDX, JC12V-100WCG2	11.5	44.0	30.0	CBar6	3500	3300	50	Univ	Clear	12	5
300	1000545	FLW, JC24V-300WA-H	13.5	55.0	30.0	CBar6	10450	3500	50	BD	Clear	10	5
300	1000846	JC24V-300WB	17.5	55.0	33.0	CBar6	6600	3050	1000	Univ	Clear	10	3




Fig.1




Fig.2




Fig.3




Fig.4




Fig.5