

# Sonnenschein A500 / A512/25G5

## INDUSTRIAL BATTERIES / NETWORK POWER

Batteries of the Sonnenschein A500 range provide high capacities for many different applications. This range has been successfully in use for over twenty years in many installations worldwide. The success of A500 batteries comes from the superior dryfit technology, available in a wide range of models to provide a solution for every power need.

Part Number: NGA5120025HS0BA

### APPLICATIONS



### SPECIFICATIONS

- Excellent energy storage capacity combined with high reliability
- Grid plate construction with high quality lead calcium alloy, specially designed for enhanced energy density
- Very low gassing due to the internal gas recombination
- Design life: »10-12 Years – Long Life« according to EUROBAT 2015 classification
- Shelf life up to 2 years at 20 °C without recharge due to the very low self discharge rate
- Superior cycling performance
- Designed in accordance with IEC 60896-21/-22
- Approval: UL (Underwriter Laboratories)
- Trouble-free transport of operational blocks, no restrictions for rail, road, sea and air transportation (IATA, DGR, clause A67)
- Manufactured in Europe in our ISO 9001 certified production plants



Design life  
10 - 12 years  
- Long Life



Block  
battery



Grid plate



Recyclable



Valve  
regulated  
lead-acid  
batteries



Proof  
against deep  
discharge



Maintenance  
free (no  
topping up)

### RECYCLE WITH EXIDE.



Exide Technologies takes pride in its commitment to a better environment. An integrated approach to manufacturing, distributing and recycling of leadacid batteries has been developed to ensure a safe and responsible life cycle for all ofits products.

## TECHNICAL CHARACTERISTICS AND DATA

<b>Nominal voltage</b>	12 V
<b>Float charge</b>	2,3 V/C @ 20 °C
<b>Capacity</b>	CP 10min 1,6V/C 20°C 514W/Bloc CC 10h 1,8V/C 20°C 22Ah
<b>Short circuit current</b>	463 A (IEC60896-21/22)
<b>Internal resistance</b>	28 mΩ (IEC60896-21/22)

<b>Terminal</b>	G-M5
<b>Terminal Torque</b>	5 Nm
<b>Container</b>	PP (Polypropylene)
<b>Temperature range</b>	-40°C to 55°C
<b>Dimensions (l x b/w x h)</b>	167 x 176 x 126 mm
<b>Weight</b>	9,6 kg
<b>Origin</b>	Büdingen, Germany


## CONSTANT POWER DISCHARGE

W @ 20 °C	3 min	5 min	10 min	15 min	20 min	30 min	45 min	1 h	90 min
1,850 V/C	535	463	387	324	278	225	170	140	105
1,800 V/C	623	555	418	360	303	240	180	146	109
1,750 V/C	689	616	454	385	320	248	185	150	111
1,700 V/C	776	652	482	395	330	253	187	151	112
1,650 V/C	854	693	501	400	335	255	188	152	112
1,600 V/C	908	725	514	403	339	256	189	153	113

## CONSTANT CURRENT DISCHARGE

A @ 20 °C	5 min	10 min	15 min	20 min	30 min	1 h	2 h	3 h	5 h	8 h	10 h
1,850 V/C	41,1	36,2	29	24,8	20,5	13,1	8	5,8	3,9	2,5	2,1
1,800 V/C	46,1	38,8	32,1	27	21,3	13,8	8,3	6	4	2,6	2,2
1,750 V/C	54,2	41,4	34,5	28,6	21,9	14,2	8,5	6,1	4	2,7	2,2
1,700 V/C	61,7	43,3	36,1	29,6	22,4	14,4	8,6	6,2	4,1	2,7	2,2
1,650 V/C	67,5	45,4	37,1	30,2	22,7	14,4	8,6	6,2	4,1	2,7	2,2
1,600 V/C	71,8	46,9	37,7	30,7	22,9	14,5	8,6	6,2	4,1	2,7	2,2

## Technical drawing



## Float Voltage vs Temperature

